



Main

| | |
|---------------------------|------------------------|
| Product or component type | Dry Sealed Transformer |
| Primary Voltage | 120 x 240 V |
| Secondary Voltage | 120/240 V |
| Full Capacity Taps | 0 |

Complementary

| | |
|------------------------------|-------------------------|
| Enclosure Code | 15B |
| Phase | 1 phase |
| Primary to Secondary Voltage | 120 x 240 V : 120/240 V |
| Power Rating | 15 kVA |
| Temperature rise | 115 °C |
| Height | 20 in |
| Width | 15 in |
| Depth | 13.5 in |
| Enclosure mounting | Wall mounted |
| Enclosure material | Painted sheet steel |

Environment

| | |
|------------------------|---------------------------|
| Enclosure Type | NEMA 3R |
| Insulation temperature | 356 °F (180 °C) |
| Product certifications | CSA cULus UL listed |

Offer Sustainability

| | |
|------------------------|----------------------------------------|
| RoHS (date code: YYWW) | Will be compliant Will be compliant |
|------------------------|----------------------------------------|

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|
