



Main

Range of product	ConneXium
Product or component type	Ethernet TCP/IP hubs
Concept	Transparent Ready
Communication port protocol	Ethernet TCP/IP
Port Ethernet	10BASE-T - 4 port(s) copper cable

Complementary


Integrated connection type	Shielded RJ45 copper cable
Transmission support medium	Twisted shielded pairs cable CAT 5E copper cable
Cable distance between devices	<= 100 m copper cable
Number of hub in cascade	4
Redundancy	P1 and P2 redundant power supplies
[Us] rated supply voltage	24 V
Supply voltage limits	18...32 V DC SELV
Power consumption in W	4.5 W
Electrical connection	Removable connector 5 ways power supply
Mounting support	35 mm symmetrical DIN rail
Marking	CE
Local signalling	1 LED per channel Ethernet link active 2 LEDs P1 P2 power supplies
Alarm output	1 voltfree contact 1 A
Alarm function	Power supply fault Switch fault Data link status
Ethernet cabling system	TF hubs
Current consumption	80 mA 24 V DC
Width	1.57 in (40 mm)
Height	4.92 in (125 mm)
Depth	3.15 in (80 mm)
Product weight	1.17 lb(US) (0.53 kg)

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environment

Ambient air temperature for operation	32...140 °F (0...60 °C)
Relative humidity	10...95 % without condensation
IP degree of protection	IP20
Standards	CSA C22.2 No 142 CUL 60950 FM 3611 Class 1 Division 2 FM 3810 UL 1604 Class 1 Division 2 UL 508 CSA C22.2 No 213 Class I Division 2
Product certifications	GL

Offer Sustainability

RoHS (date code: YYWW)	Compliant  Schneider Electric declaration of conformity
------------------------	---

Contractual warranty

Warranty period	18 months
-----------------	-----------