





Transformer, dry type, encapsulated, 5kVA, 1 phase, 480V primary, 120/240V secondary, 52X, 115C rise

4X5S40FSS



! Discontinued on: Jun 30, 2023

### Main

Product Or Component Type	Dry Sealed Transformer	
Primary To Secondary Voltage	240 x 480 V 120/240 V	
Full Capacity Taps	2 5 % FCBN	

## Complementary

Enclosure Code	52X	
Phase	1 phase	
Power Rating	5 kVA	
Temperature Rise	115 °C	
Height	12 in (304.80 mm)	
Width	13.75 in (349.25 mm)	
Depth	13.75 in (349.25 mm)	
Enclosure Mounting	Wall mounted	
Enclosure Material	Stainless steel	

### **Environment**

Enclosure Type	NEMA 4X
Insulation Temperature	356 °F (180 °C)
Product Certifications	CSA cULus UL listed

# **Packing Units**

Unit Type Of Package 1	PCE	
Number Of Units In Package 1	1	
Package 1 Height	13.25 in (33.655 cm)	
Package 1 Width	11.25 in (28.575 cm)	
Package 1 Length	14.25 in (36.195 cm)	
Package 1 Weight	115.00 lb(US) (52.163 kg)	



**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

### Well-being performance

<b>⊘</b>	Reach Free Of Svhc	
<b>⊘</b>	Toxic Heavy Metal Free	
<b>⊘</b>	Mercury Free	
<b>⊘</b>	Rohs Exemption Information Y	res
<b>Ø</b>	Pvc Free	

### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration  Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations