



Transformer, dry type, encapsulated, 0.05kVA, 1 phase, 240x480V primary, 120/240V secondary, 1A, 55C rise

50SV1A

Main

Product Or Component Type	Dry Sealed Transformer	
Primary To Secondary Voltage	240 x 480 V 120/240 V	
Full Capacity Taps	0	

Complementary

Enclosure Code	1A	
Phase	1 phase	
Power Rating	0.05 kVA	
Temperature Rise	55 °C	
Height	5 in (127.00 mm)	
Width	4.47 in (113.54 mm)	
Depth	3.44 in (87.38 mm)	
Enclosure Mounting	Wall mounted	
Enclosure Material	Painted sheet steel	

Environment

Enclosure Type	NEMA 3R
Insulation Temperature	221 °F (105 °C)
Product Certifications	UL listed cULus CSA

Packing Units

Unit Type Of Package 1	PCE	
Number Of Units In Package 1	1	
Package 1 Height	6.60 in (16.764 cm)	
Package 1 Width	7.00 in (17.78 cm)	
Package 1 Length	8.10 in (20.574 cm)	
Package 1 Weight	5.51 lb(US) (2.499 kg)	

Contractual warranty

Warranty	18 months
----------	-----------



Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

⊘	Reach Free Of Svhc	
⊘	Toxic Heavy Metal Free	
⊘	Mercury Free	
⊘	Rohs Exemption Information Yes	
Ø	Pvc Free	

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations