



Contactor, Definite Purpose, 30A, 4 pole, 20HP at 575VAC, 3 phase, 24/24VAC 50/60Hz coil, open

8910DPA34V14

Main

Product Or Component Type	Definite Purpose Contactor
[In] Rated Current	30 A
Number Of Poles	4P
Pole Contact Composition	4 NO
Range Of Product	DPA

Complementary

Motor Power Hp	2 hp 115 V AC, 1 phase 5 hp 230 V AC, 1 phase 10 hp 230 V AC, 3 phases 15 hp 460 V AC, 3 phases 20 hp 575 V AC, 3 phases
Locked Rotor Rated Current	150 A 460 V AC 120 A 575 V AC 180 A 277 V AC
[Ue] Rated Operational Voltage	600 V AC
[Uc] Control Circuit Voltage	24 V AC 50/60 Hz
Network Number Of Phases	3 phases
Electrical Connection	Quick connect terminals Binder head

Environment

Product Certifications	UL recognized
	CSA

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	3.10 in (7.874 cm)
Package 1 Width	4.10 in (10.414 cm)
Package 1 Length	3.20 in (8.128 cm)
Package 1 Weight	20.96 oz (594.206 g)
Unit Type Of Package 2	CAR
Number Of Units In Package 2	8
Package 2 Height	7.00 in (17.78 cm)
Package 2 Width	6.90 in (17.526 cm)

Package 2 Length	8.40 in (21.336 cm)
Package 2 Weight	12.00 lb(US) (5.443 kg)

Contractual warranty

Warranty 18 months

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Well-being performance

Mercury Free		
Rohs Exemption Information	Yes	
Reach Regulation	REACh Declaration	
Eu Rohs Directive	Compliant with Exemptions	
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information	