



Contactor, Definite Purpose, 40A, 3 pole, 25HP at 575VAC, 3 phase, 550/600VAC 50/60Hz coil, open

8910DPA43V07

#### Main

| Product Or Component Type | Definite Purpose Contactor |
|---------------------------|----------------------------|
| [In] Rated Current        | 40 A                       |
| Number Of Poles           | 3P                         |
| Pole Contact Composition  | 3 NO                       |
| Range Of Product          | DPA                        |

### **Complementary**

| Motor Power Hp                 | 3 hp 115 V AC, 1 phase<br>7.5 hp 230 V AC, 1 phase<br>10 hp 230 V AC, 3 phases<br>20 hp 460 V AC, 3 phases<br>25 hp 575 V AC, 3 phases |
|--------------------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| Locked Rotor Rated Current     | 240 A 277 V AC<br>200 A 460 V AC<br>160 A 575 V AC                                                                                     |
| [Ue] Rated Operational Voltage | 600 V AC                                                                                                                               |
| [Uc] Control Circuit Voltage   | 550 V AC 50 Hz<br>600 V AC 60 Hz                                                                                                       |
| Network Number Of Phases       | 3 phases                                                                                                                               |
| Electrical Connection          | Quick connect terminals Box lugs                                                                                                       |

#### **Environment**

| <b>Product Certifications</b> | UL recognized |  |
|-------------------------------|---------------|--|
|                               | CSA           |  |

## **Packing Units**

| Unit Type Of Package 1       | PCE                  |
|------------------------------|----------------------|
| Number Of Units In Package 1 | 1                    |
| Package 1 Height             | 2.60 in (6.604 cm)   |
| Package 1 Width              | 3.20 in (8.128 cm)   |
| Package 1 Length             | 4.30 in (10.922 cm)  |
| Package 1 Weight             | 18.88 oz (535.239 g) |

# **Contractual warranty**

| Warranty 18 months |  |
|--------------------|--|
|--------------------|--|

## Sustainability

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

#### Well-being performance

| vvon being periormanie |                            |                                                                                                     |
|------------------------|----------------------------|-----------------------------------------------------------------------------------------------------|
| <b>②</b>               | Mercury Free               |                                                                                                     |
| <b>⊘</b>               | Rohs Exemption Information | Yes                                                                                                 |
| Rea                    | ch Regulation              | REACh Declaration                                                                                   |
| Eu f                   | Rohs Directive             | Compliant with Exemptions                                                                           |
| Chir                   | na Rohs Regulation         | China RoHS declaration  Product out of China RoHS scope. Substance declaration for your information |