Specifications

SQUARE D



Contactor, Definite Purpose, 60A, 2 pole, 10HP at 230VAC, 1 phase, 110/120VAC 50/60Hz coil, open

8910DPA62V02

Main

Product Or Component Type	Definite Purpose Contactor
[In] Rated Current	60 A
Number Of Poles	2P
Pole Contact Composition	2 NO
Range Of Product	DPA

Complementary

Motor Power Hp	5 hp 115 V AC, 1 phase 10 hp 230 V AC, 1 phase
Locked Rotor Rated Current	360 A 277 V AC 300 A 460 V AC 240 A 575 V AC
[Ue] Rated Operational Voltage	600 V AC
[Uc] Control Circuit Voltage	120 V AC 60 Hz 110 V AC 50 Hz
Network Number Of Phases	1 phase
Electrical Connection	Quick connect terminals Box lugs

Environment

Product Certifications	UL recognized
	CSA

Packing Units

-	
Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	3.80 in (9.652 cm)
Package 1 Width	4.50 in (11.43 cm)
Package 1 Length	2.70 in (6.858 cm)
Package 1 Weight	23.36 oz (662.245 g)
Unit Type Of Package 2	CAR
Number Of Units In Package 2	8
Package 2 Height	8.10 in (20.574 cm)
Package 2 Width	5.70 in (14.478 cm)
Package 2 Length	9.00 in (22.86 cm)

Package 2 Weight

12.05 lb(US) (5.466 kg)

Contractual warranty

Warranty

18 months

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Well-being performance

Mercury Free	
Rohs Exemption Information	Yes
Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information

Dimensions Drawings

Approximate Dimensions

