Product data sheet

Specifications

SQUARE D



Contactor, Definite Purpose, 60A, 3 pole, 30 HP at 575 VAC, 3 phase, 110/120 VAC 50/60 Hz coil, open, UL Listed

8910DPA63V02U1

() Discontinued

() Discontinued on: Jun 30, 2023

Main

Product Or Component Type	Definite Purpose Contactor
[In] Rated Current	60 A
Number Of Poles	3P
Pole Contact Composition	3 NO
Range Of Product	DPA

Complementary

Motor Power Hp	5 hp 115 V AC, 1 phase 10 hp 230 V AC, 1 phase 30 hp 460 V AC, 3 phases
	30 hp 575 V AC, 3 phases
	25 hp 230 V AC, 3 phases
Locked Rotor Rated Current	360 A 277 V AC
	300 A 460 V AC
	240 A 575 V AC
[Ue] Rated Operational Voltage	600 V AC
[Uc] Control Circuit Voltage	120 V AC 60 Hz
	110 V AC 50 Hz
Network Number Of Phases	3 phases
Electrical Connection	Box lugs

Environment

Product Certifications	UL listed CSA

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	3.80 in (9.652 cm)
Package 1 Width	4.30 in (10.922 cm)
Package 1 Length	2.70 in (6.858 cm)
Package 1 Weight	25.28 oz (716.676 g)

Contractual warranty

Warranty

18 months

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Well-being performance

Mercury Free	
Rohs Exemption Information	Yes
Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information