# Product data sheet





## Backplane, Modicon X80, 6 slots, panel, mounitng plate or DIN rail mounting

BMXXBP0600

### Main

Range Of Product	Modicon X80
Product Or Component Type	Backplane

### Complementary

,	
Number Of Slots	6 bus X
Product Compatibility	BMXP34 processor BMXCPS power supply
	I/O module
	Specific application module
Power Consumption In W	1.68 W
Electrical Connection	1 connector (XBE) expansion module
Fixing Mode	By 4 M4/M5/M6 screws panel By 4 M4/M5/M6 screws mounting plate By clips 35 mm symmetrical DIN rail
Height	4.08 in (103.7 mm)
Width	12.11 in (307.6 mm)
Depth	0.75 in (19 mm)
Net Weight	1.74 lb(US) (0.79 kg)

### **Environment**

Ip Degree Of Protection	IP20		
Ambient Air Temperature For Operation	32140 °F (060 °C)		
Relative Humidity	1095 % without condensation		
Directives	2014/35/EU - low voltage directive 2014/30/EU - electromagnetic compatibility		
Product Certifications	CE UL CSA RCM EAC UKCA Merchant Navy		
Standards	EN/IEC 61131-2 EN/IEC 61010-2-201 UL 61010-2-201 CSA C22.2 No 61010-2-201		

EN/IEC 61000-6-5, interface type 1 and type 2

EN/IEC 61850-3, location G

**Packing Units** 



IACS E10



Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	2.64 in (6.700 cm)
Package 1 Width	6.02 in (15.300 cm)
Package 1 Length	15.55 in (39.500 cm)
Package 1 Weight	29.45 oz (835.000 g)
Unit Type Of Package 2	S04
Number Of Units In Package 2	9
Package 2 Height	11.81 in (30.000 cm)
Package 2 Width	15.75 in (40.000 cm)
Package 2 Length	23.62 in (60.000 cm)
Package 2 Weight	18.49 lb(US) (8.385 kg)
Unit Type Of Package 3	P06
Number Of Units In Package 3	54
Package 3 Height	41.34 in (105.000 cm)
Package 3 Width	23.62 in (60.000 cm)
Package 3 Length	31.50 in (80.000 cm)
Package 3 Weight	132.63 lb(US) (60.160 kg)

## **Contractual warranty**

Warranty 18 months



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

### Well-being performance



Mercury Free



Rohs Exemption Information

Yes

### **Certifications & Standards**


Reach Regulation	REACh Declaration		
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)		
China Rohs Regulation	China RoHS declaration		
Environmental Disclosure	Product Environmental Profile		
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins		
Circularity Profile	End of Life Information		

## **Product data sheet**

### BMXXBP0600

### **Dimensions Drawings**

### **Dimensions**




#### BMXXBP0600

### Mounting and Clearance

#### **Minimum Clearance**

Minimum Clearance of a typical installation in a cabinet with ducts




- a Side clearance: > 40 mm (1.57 in.)
- **b** Top and bottom clearance with surrounding objects: > 20 mm (0.79 in.)
- 1 Installation or casing
- 2 Wiring duct or tray

#### Mounting on DIN rail

Symmetric DIN rail		5, 5, 5, 5, 5, 5, 5, 5, 5, 5, 5, 5, 5, 5	
Type A	Туре В	Double-profile DIN rail	
35.0 	mm 61.0 88:1 7.2 0.28	7.2 0.28 98.1 0.59	


NOTE: When mounted on a type B symmetric DIN rail, the rack withstands less mechanical stress.

#### **Mounting on panels**



Rack Type	а	b	
X Bus racks	BMXXBP0400 BMXXBP0400H	202.1 mm (7.957 in)	214.8 mm (8.457 in)
	BMXXBP0600 BMXXBP0600H	267.5 mm (10.531 in)	280 mm (11.023 in)
	BMXXBP0800 BMXXBP0800H	332.5 mm (13.091 in)	345.2 mm (13.591 in)
	BMXXBP1200 BMXXBP1200H	462.9 mm (18.224 in)	475.6 mm (18.724 in)

### Mounting on Telequick mounting plate



1 Telequick plate 2 Clip-on nuts

**NOTE:** The two right side screws are accessible until there is no rack extender module installed