



Safety switch, double throw, non fusible, 200A, 480 VAC/250 VDC, 3 poles, 15 hp, NEMA 3R with bolt on hub provision

C82344RB

Main

Product	Double Throw Safety Switch
Current Rating	200 A
Certifications	CSA
Enclosure Rating	NEMA 3R galvannealed steel
Disconnect Type	Non-fusible disconnect
Mounting Type	Surface
Number Of Poles	3
Voltage Rating	250 V DC 480 V AC
Wire Size	AWG 6300 kcmil copper or aluminum

Complementary

Motor Power Hp	15 hp at 480 V AC 5060 Hz for 3 phases motors	
Tightening Torque	275 lbf.in (31.07 N.m) 0.020.20 in² (13.30127 mm²) AWG 6250 kcmil)	
Width	24 in (609.60 mm)	
Height	32.5 in (825.50 mm)	
Depth	10.63 in (270.00 mm)	

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	10.71 in (27.2 cm)
Package 1 Width	22.72 in (57.7 cm)
Package 1 Length	33.90 in (86.1 cm)
Package 1 Weight	77.01 lb(US) (34.93 kg)



Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

Ø	Reach Free Of Svhc	
②	Toxic Heavy Metal Free	
9	Mercury Free	
⊘	Rohs Exemption Information	Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations