



Safety switch, heavy duty, fusible, 100A, 240VAC, 250VDC, 2 poles, 30HP, NEMA 1, neutral

CH223N

- ! Discontinued on: Jul 4, 2023
- ! End-of-service on: Aug 5, 2023

### Main

Product	Single Throw Safety Switch
Disconnect Type	Fusible disconnect
Number Of Poles	2
Electrical Connection	Lugs
Duty Rating	Heavy duty

## Complementary

Line Rated Current	100 A
Factory Installed Neutral	Neutral (factory installed)
Mounting Type	Surface
Voltage Rating	240 V DC
	250 V AC
Motor Power Hp	7.5 hp at 240 V AC 5060 Hz for 1 phase motors
	15 hp at 240 V AC 5060 kHz for 3 phases motors
	15 hp at 240 V AC 5060 kHz for 1 phase motors
	30 hp at 240 V AC 5060 kHz for 3 phases motors
	20 hp at 250 V DC
Wire Size	AWG 12AWG 1/0 aluminum
	AWG 14AWG 1/0 copper
Tightening Torque	50 lbf.in (5.65 N.m) AWG 3AWG 1)
	45 lbf.in (5.08 N.m) AWG 6AWG 4)
	40 lbf.in (4.52 N.m) 0.01 in <sup>2</sup> (8.367 mm <sup>2</sup> ) AWG 8)
	40 lbf.in (4.52 N.m) AWG 8)
	35 lbf.in (3.95 N.m) 0.000.01 in <sup>2</sup> (2.065.261 mm <sup>2</sup> ) AWG 14AWG 10)
	35 lbf.in (3.95 N.m) AWG 14AWG 10)
Height	21.25 in (539.75 mm)
Width	10.5 in (266.70 mm)
Depth	6.38 in (162.05 mm)

#### **Environment**

Certifications	CSA
Enclosure Rating	NEMA 1 galvannealed steel

# **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1

Package 1 Height	7.20 in (18.288 cm)
Package 1 Width	10.70 in (27.178 cm)
Package 1 Length	23.30 in (59.182 cm)
Package 1 Weight	17.28 lb(US) (7.838 ka)



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

### Well-being performance



### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration  Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations