





Generator panel, QO, 1 phase, 4 spaces, 8 circuits, 60A main breaker with interlock, NEMA1, surface cover door, CSA

CQO48M60DSGP

Main

Marketing Trade Name	QO
Product Type	Panel
Cover Type	Surface cover

Complementary

Tightening Torque	Cover 20 lb.in
Load Center Type	Main Breaker
Rated Current	60 A
Number Of Spaces	4
Maximum Number Of Single Pole Circuits	4
Maximum Number Of Tandem Breakers	8
Number Of Phases	1 phase
Voltage Rating	120/240 V AC
Wire Size	AWG 8AWG 2 aluminum/copper
Electrical Connection	Lugs
Wiring Configuration	3-wire
Box Number	4
Height	12.45 in (316.23 mm)
Width	8.76 in (222.50 mm)
Depth	3.75 in (95.25 mm)

Environment

Enclosure Rating	NEMA 1 indoor generator	
Ambient Air Temperature For Operation	23 °F (-5 °C) 104 °F (40 °C)	
Product Certifications	cULus CSA	

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	4.41 in (11.2 cm)
Package 1 Width	10.79 in (27.4 cm)

Package 1 Length	14.41 in (36.6 cm)
Package 1 Weight	9.50 lb(US) (4.31 kg)



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

⊘	Reach Free Of Svhc	
9	Toxic Heavy Metal Free	
②	Mercury Free	
⊘	Rohs Exemption Information	Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations