

Mini circuit breaker, E-Frame, 70A, 3 pole, 600Y/347 VAC, 25 kA max, bolt on

EDB36070

#### Main

Range Of Product	125 A Frame EDB-EGB-EJB
Product Or Component Type	Circuit-breaker
Device Short Name	EDB
Module Type	E-Frame
Trip Unit Rating	1800 A

# Complementary

[In] Rated Current	70 A
Maximum Operating Voltage	600Y/347 V AC
Awg Gauge	AWG 12AWG 2/0 aluminum AWG 14AWG 2/0 copper
Breaking Capacity	14 kA 600Y/347 V AC
Circuit Breaker Application	HACR rated
Electrical Connection	Lugs aluminum
Holding Current	630 A
Local Signalling	Trip indicator
Mounting Mode	Bolt-on
Number Of Poles	3
Number Of Spaces	3
Number Of Spaces Required	3
Product Destination	NF panelboard
Protection Type	Overload Short-circuit
Protection Type  Trip Unit Technology	
	Short-circuit
Trip Unit Technology	Short-circuit Thermal-magnetic
Trip Unit Technology  Breaking Capacity Code	Short-circuit  Thermal-magnetic  D  34.52 lbf.in (3.9 N.m) 0.000.01 in² (2.56 mm²) AWG 14AWG 10)
Trip Unit Technology  Breaking Capacity Code  Tightening Torque	Short-circuit  Thermal-magnetic  D  34.52 lbf.in (3.9 N.m) 0.000.01 in² (2.56 mm²) AWG 14AWG 10) 49.56 lbf.in (5.6 N.m) 0.020.11 in² (1070 mm²) AWG 8AWG 2/0)
Trip Unit Technology  Breaking Capacity Code  Tightening Torque  Height	Short-circuit  Thermal-magnetic  D  34.52 lbf.in (3.9 N.m) 0.000.01 in² (2.56 mm²) AWG 14AWG 10) 49.56 lbf.in (5.6 N.m) 0.020.11 in² (1070 mm²) AWG 8AWG 2/0)  5.66 in (143.76 mm)

## **Environment**

Product Certifications	cULus
Ambient Air Temperature For Operation	104 °F (40 °C)
Pooking Units	

#### **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	4.49 in (11.4 cm)
Package 1 Width	6.10 in (15.5 cm)
Package 1 Length	9.88 in (25.1 cm)
Package 1 Weight	3.55 lb(US) (1.61 kg)

## Sustainability

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

## Well-being performance

Mercury Free	
Pulse Executive Information	
Rohs Exemption Information	Yes
Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration
	Product out of China RoHS scope. Substance declaration for your information