Specifications

SQUARE D



Transformer Dry Type 30kVA 480D208Y120

EE30T3HFISCUNL

- () Discontinued on: Oct 30, 2021
- (!) End-of-service on: Dec 1, 2021
- ① Discontinued Service only

Main

Product Non-Linear Transformer Enclosure Code 18D Enclosure Type NEMA 2 Insulation Temperature 428 °F (220 °C) K-Factor K-4 Phase 3 phases Primary Voltage 480 V delta	
Enclosure Type NEMA 2 Insulation Temperature 428 °F (220 °C) K-Factor K-4 Phase 3 phases	
Insulation Temperature 428 °F (220 °C) K-Factor K-4 Phase 3 phases	
K-Factor K-4 Phase 3 phases	
Phase 3 phases	
Primary Voltage 480 V delta	
Power Rating 30 kVA	
Secondary Voltage 208Y/120 V	
Full Capacity Taps 6 2.5 % 2+ 4-	
Temperature Rise 115 °C	
Winding Material Copper	

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	36.30 in (92.202 cm)
Package 1 Width	21.40 in (54.356 cm)
Package 1 Length	21.10 in (53.594 cm)
Package 1 Weight	436.00 lb(US) (197.766 kg)

Contractual warranty

Warranty

18 months

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency

Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Environmental Disclosure	Product Environmental Profile