

# 30KVA TP1 480 DELTA-208Y/120

EE30T3HISCUNLP

! To be discontinued on: Apr 30, 2024

#### Main

Product	Non-Linear Transformer
Enclosure Code	18D
Enclosure Type	NEMA 2
Insulation Temperature	428 °F (220 °C)
K-Factor	K-13
Phase	3 phases
Primary Voltage	480 V delta
Power Rating	30 kVA
Secondary Voltage	208Y/120 V
Full Capacity Taps	6 2.5 % 2+ 4-
Temperature Rise	150 °C
Winding Material	Copper

### **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	30.00 in (76.2 cm)
Package 1 Width	20.00 in (50.8 cm)
Package 1 Length	20.00 in (50.8 cm)
Package 1 Weight	340.00 lb(US) (154.221 kg)

## **Contractual warranty**

Warranty 18 months

### Sustainability

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency

Eu Rohs Directive Pro-active compliance (Product out of EU RoHS legal scope)

**EU RoHS Declaration** 

Environmental Disclosure Product Environmental Profile