Product data sheet

Specifications



Transformer, dry type, 500kVA, 3 phase, 480V delta primary, 208Y/ 120V secondary, 30D, 150C rise

EE500T68H

	_:	
IVI	ai	n

Product	Energy Efficient Transformer
Enclosure Code	30D
Enclosure Type	NEMA 2
Insulation Temperature	428 °F (220 °C)
Phase	3 phases
Primary Voltage	480 V delta
Power Rating	500 kVA
Secondary Voltage	208Y/120 V
Full Capacity Taps	4 2.5 % 2+ 2-
Temperature Rise	150 °C
Winding Material	Aluminium

Complementary

Height	71 in (1803.40 mm)
Width	48 in (1219.20 mm)
Depth	36 in (914.40 mm)
Net Weight	1870.00 lb(US) (848.218 kg)

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1

Contractual warranty Warranty 18 r

18 months

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Reach Free Of Svhc
Toxic Heavy Metal Free
Mercury Free
Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations