

Product data sheet

Specifications

SQUARE D



Transformer, dry type, 500kVA, 3 phase, 480V delta primary, 208Y/120V secondary, 30D, 80C rise, Cu

EE500T68HBCU

Discontinued

Discontinued on: Nov 1, 2022

Main

Product	Energy Efficient Transformer
Enclosure Code	30D
Enclosure Type	NEMA 2
Insulation Temperature	428 °F (220 °C)
Phase	3 phases
Primary Voltage	480 V delta
Power Rating	500 kVA
Secondary Voltage	208Y/120 V
Full Capacity Taps	4 2.5 % 2+ 2-
Temperature Rise	80 °C
Winding Material	Copper

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Weight	2578.00 lb(US) (1169.361 kg)

Contractual warranty

Warranty	18 months
----------	-----------

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Sustainability

Green Premium™ label is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product’s sustainability >](#)



Transparency

Eu Rohs Directive

Pro-active compliance (Product out of EU RoHS legal scope)

[EU RoHS Declaration](#)

Environmental Disclosure

[Product Environmental Profile](#)