



Transformer, dry type, 75kVA, 3 phase, 600V delta primary, 208Y/ 120V secondary, 20D, 150C rise, Cu

EE75T65HCU

(!) Discontinued on: Oct 11, 2022

#### Main

Product	Energy Efficient Transformer	
Enclosure Code	20D	
Enclosure Type	NEMA 2	
Insulation Temperature	428 °F (220 °C)	
Phase	3 phases	
Primary Voltage	600 V delta	
Power Rating	75 kVA	
Secondary Voltage	208Y/120 V	
Temperature Rise	150 °C	
Winding Material	Copper	

## **Packing Units**

Unit Type Of Package 1	PCE	
Number Of Units In Package 1	1	
Package 1 Height	42.99 in (109.2 cm)	
Package 1 Width	31.50 in (80.0 cm)	
Package 1 Length	21.50 in (54.6 cm)	
Package 1 Weight	968.17 lb(US) (439.155 kg)	

# **Contractual warranty**

Warranty 18 months



**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

### Well-being performance

<b>⊘</b>	Reach Free Of Svhc	
<b>⊘</b>	Toxic Heavy Metal Free	
<b>⊘</b>	Mercury Free	
<b>⊘</b>	Rohs Exemption Information Yes	
<b>Ø</b>	Pvc Free	

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration  Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations