



Mini circuit breaker, E-Frame, 30A, 2 pole, 480Y/277 VAC, 65 kA max, bolt on

EGB24030

Main

| Range Of Product | 125 A Frame EDB-EGB-EJB |
|---------------------------|---------------------------|
| Product Or Component Type | Miniature circuit-breaker |
| Device Short Name | EGB |
| Module Type | E-Frame |
| Trip Unit Rating | 875 A |

Complementary

| Complementary | |
|-----------------------------|---|
| [In] Rated Current | 30 A |
| Maximum Operating Voltage | 480Y/277 V AC |
| Awg Gauge | AWG 12AWG 6 aluminum AWG 14AWG 6 copper |
| Breaking Capacity | 35 kA 277 V AC 65 kA 240 V AC 35 kA 480Y/277 V AC 65 kA 120 V AC 65 kA 120/240 V AC |
| Circuit Breaker Application | HID rated HACR rated |
| Electrical Connection | Lugs aluminum |
| Holding Current | 270 A |
| Local Signalling | Trip indicator |
| Mounting Mode | Bolt-on |
| Number Of Poles | 2 |
| Number Of Spaces | 2 |
| Number Of Spaces Required | 2 |
| Product Destination | NF panelboard |
| Protection Type | Short-circuit Overload |
| Trip Unit Technology | Thermal-magnetic |
| Breaking Capacity Code | G |
| Tightening Torque | 30.09 lbf.in (3.4 N.m) 0.000.02 in² (2.516 mm²) AWG 14AWG 6) |
| Height | 5.66 in (143.76 mm) |
| Width | 1.96 in (49.78 mm) |
| Depth | 4.05 in (102.87 mm) |
| Net Weight | 3 lb(US) (1.36 kg) |

Environment

| Product Certifications | cULus |
|---------------------------------------|----------------|
| Ambient Air Temperature For Operation | 104 °F (40 °C) |

Packing Units

| • | |
|------------------------------|----------------------|
| Unit Type Of Package 1 | PCE |
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 3.58 in (9.1 cm) |
| Package 1 Width | 6.10 in (15.5 cm) |
| Package 1 Length | 9.80 in (24.9 cm) |
| Package 1 Weight | 2.65 lb(US) (1.2 kg) |

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Well-being performance

| Wen being performance | | |
|----------------------------|---|--|
| Mercury Free | | |
| Rohs Exemption Information | Yes | |
| Reach Regulation | REACh Declaration | |
| Eu Rohs Directive | Pro-active compliance (Product out of EU RoHS legal scope) | |
| China Rohs Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information | |