

Product data sheet

Specifications

SQUARE D



Mini circuit breaker, E-Frame, 15A,
1 pole, 600Y/347 VAC, 100 kA
max, bolt on

EJB16015

Main

| | |
|---------------------------|-------------------------|
| Range Of Product | 125 A Frame EDB-EGB-EJB |
| Product Or Component Type | Circuit-breaker |
| Device Short Name | EJB |
| Module Type | E-Frame |
| Trip Unit Rating | 875 A |

Complementary

| | |
|-----------------------------|---|
| [In] Rated Current | 15 A |
| Maximum Operating Voltage | 600Y/347 V AC |
| Awg Gauge | AWG 12...AWG 6 aluminum AWG 14...AWG 6 copper |
| Breaking Capacity | 25 kA 600Y/347 V AC |
| Circuit Breaker Application | HACR rated |
| Electrical Connection | Lugs aluminum |
| Holding Current | 270 A |
| Local Signalling | Trip indicator |
| Mounting Mode | Bolt-on |
| Number Of Poles | 1 |
| Number Of Spaces | 1 |
| Number Of Spaces Required | 1 |
| Product Destination | NF panelboard |
| Protection Type | Short-circuit Overload |
| Trip Unit Technology | Thermal-magnetic |
| Breaking Capacity Code | J |
| Tightening Torque | 30.09 lbf.in (3.4 N.m) 0.00...0.02 in² (2.5...16 mm²) AWG 14...AWG 6) |
| Height | 5.66 in (143.76 mm) |
| Width | 0.98 in (24.89 mm) |
| Depth | 4.05 in (102.87 mm) |
| Net Weight | 2 lb(US) (0.91 kg) |

Environment

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|---------------------------------------|----------------|
| Product Certifications | cULus |
| Ambient Air Temperature For Operation | 104 °F (40 °C) |

Packing Units

| | |
|------------------------------|--------------------|
| Unit Type Of Package 1 | PCE |
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 1.81 in (4.6 cm) |
| Package 1 Width | 6.18 in (15.7 cm) |
| Package 1 Length | 10.51 in (26.7 cm) |
| Package 1 Weight | 21.76 oz (616.9 g) |

Sustainability

Green Premium™ label is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product’s sustainability >](#)

Well-being performance

| | |
|--|---|
|  Mercury Free | |
|  Rohs Exemption Information | Yes |
| Reach Regulation | REACH Declaration |
| Eu Rohs Directive | Pro-active compliance (Product out of EU RoHS legal scope) |
| China Rohs Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information |