



Mini circuit breaker, E-Frame, 50A, 2 pole, 600Y/347 VAC, 100 kA max, bolt on

EJB26050

Main

| Range Of Product | 125 A Frame EDB-EGB-EJB |
|---------------------------|-------------------------|
| Product Or Component Type | Circuit-breaker |
| Device Short Name | EJB |
| Module Type | E-Frame |
| Trip Unit Rating | 1800 A |

Complementary

| [In] Rated Current | 50 A |
|-----------------------------|---|
| Maximum Operating Voltage | 600Y/347 V AC |
| Awg Gauge | AWG 12AWG 2/0 aluminum AWG 14AWG 2/0 copper |
| Breaking Capacity | 25 kA 600Y/347 V AC |
| Circuit Breaker Application | HACR rated |
| Electrical Connection | Lugs aluminum |
| Holding Current | 630 A |
| Local Signalling | Trip indicator |
| Mounting Mode | Bolt-on |
| Number Of Poles | 2 |
| Number Of Spaces | 2 |
| Number Of Spaces Required | 2 |
| Product Destination | NF panelboard |
| Protection Type | Short-circuit Overload |
| Trip Unit Technology | Thermal-magnetic |
| Breaking Capacity Code | J |
| Tightening Torque | 34.52 lbf.in (3.9 N.m) 0.000.01 in² (2.56 mm²) AWG 14AWG 10) 49.56 lbf.in (5.6 N.m) 0.020.11 in² (1070 mm²) AWG 8AWG 2/0) |
| Height | 5.66 in (143.76 mm) |
| Width | 1.96 in (49.78 mm) |
| Depth | 4.05 in (102.87 mm) |
| Net Weight | 3 lb(US) (1.36 kg) |

Environment

| Product Certifications | cULus |
|---------------------------------------|----------------|
| Ambient Air Temperature For Operation | 104 °F (40 °C) |
| Pooking Units | |

Packing Units

| Unit Type Of Package 1 | PCE |
|------------------------------|-----------------------|
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 3.70 in (9.398 cm) |
| Package 1 Width | 6.00 in (15.24 cm) |
| Package 1 Length | 9.80 in (24.892 cm) |
| Package 1 Weight | 2.54 lb(US) (1.15 kg) |

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Well-being performance

| Mercury Free | |
|-----------------------------|---|
| Pulse Formation Information | |
| Rohs Exemption Information | Yes |
| | |
| Reach Regulation | REACh Declaration |
| Eu Rohs Directive | Pro-active compliance (Product out of EU RoHS legal scope) |
| China Rohs Regulation | China RoHS declaration |
| | Product out of China RoHS scope. Substance declaration for your information |