



Mini circuit breaker, E-Frame, 110A, 3 pole, 480Y/277VAC, 100kA max, bolt on

EJB34110

Main

| Range Of Product | 125 A Frame EDB-EGB-EJB | |
|---------------------------|---------------------------|--|
| Product Or Component Type | Miniature circuit-breaker | |
| Device Short Name | EJB | |
| Module Type | E-Frame | |
| Trip Unit Rating | 2300 A | |

Complementary

| Complementary | |
|-----------------------------|---|
| [In] Rated Current | 110 A |
| Maximum Operating Voltage | 480Y/277 V AC |
| Awg Gauge | AWG 12AWG 2/0 aluminum AWG 14AWG 2/0 copper |
| Breaking Capacity | 65 kA 277 V AC 100 kA 240 V AC 65 kA 480Y/277 V AC 100 kA 120 V AC 100 kA 120/240 V AC |
| Circuit Breaker Application | HACR rated |
| Electrical Connection | Lugs aluminum |
| Holding Current | 1000 A |
| Local Signalling | Trip indicator |
| Mounting Mode | Bolt-on |
| Number Of Poles | 3 |
| Number Of Spaces | 3 |
| Number Of Spaces Required | 3 |
| Product Destination | NF panelboard |
| Protection Type | Overload Short-circuit |
| Trip Unit Technology | Thermal-magnetic |
| Breaking Capacity Code | J |
| Tightening Torque | 34.52 lbf.in (3.9 N.m) 0.000.01 in² (2.56 mm²) AWG 14AWG 10) 49.56 lbf.in (5.6 N.m) 0.020.11 in² (1070 mm²) AWG 8AWG 2/0) |
| Height | 5.66 in (143.76 mm) |
| Width | 2.94 in (74.68 mm) |
| Depth | 4.05 in (102.87 mm) |
| Net Weight | 4 lb(US) (1.81 kg) |

Environment

| Product Certifications | cULus |
|---------------------------------------|----------------|
| Ambient Air Temperature For Operation | 104 °F (40 °C) |

Packing Units

| Unit Type Of Package 1 | PCE |
|------------------------------|------------------------|
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 4.80 in (12.192 cm) |
| Package 1 Width | 6.20 in (15.748 cm) |
| Package 1 Length | 9.90 in (25.146 cm) |
| Package 1 Weight | 3.47 lb(US) (1.575 kg) |

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Well-being performance

| Mercury Free | |
|-----------------------------|---|
| Pulse Formation Information | |
| Rohs Exemption Information | Yes |
| | |
| Reach Regulation | REACh Declaration |
| Eu Rohs Directive | Pro-active compliance (Product out of EU RoHS legal scope) |
| China Rohs Regulation | China RoHS declaration |
| | Product out of China RoHS scope. Substance declaration for your information |