# Product data sheet

Specifications





## PowerLogic HU250 RS232/422/485 interface box, RJ45

EMS59151

() Discontinued on: Jun 30, 2023

① Discontinued

#### Main

| Range Of Product          | PowerLogic T300               |
|---------------------------|-------------------------------|
| Device Short Name         | HU250-RS                      |
| Product Or Component Type | Modem communication interface |

### Complementary

| Connector Type             | RJ45                    |
|----------------------------|-------------------------|
| Communication Port Support | RS485<br>RS422<br>RS232 |
| Transmission Rate          | 38400 bit/s             |

#### Environment

| Ik Degree Of Protection                  | IK07 conforming to IEC 62262      |
|--|-----------------------------------|
| Relative Humidity                        | 95 % conforming to IEC 60068-2-30 |
| Ambient Air Temperature For<br>Operation | -40185 °F (-4085 °C)              |
| Ambient Air Temperature For<br>Storage   | -40185 °F (-4085 °C)              |
| Fire Resistance                          | 1562 °F (850 °C)                  |
| Operating Altitude                       | 2000 m                            |
| Product Certifications                   | CE                                |
| Height                                   | 1.18 in (30 mm)                   |
| Width                                    | 4.53 in (115 mm)                  |
| Depth                                    | 5.24 in (133 mm)                  |
| Net Weight                               | 0.23 lb(US) (0.105 kg)            |

## **Packing Units**

| Unit Type Of Package 1       | PCE               |
|------------------------------|-------------------|
| Number Of Units In Package 1 | 1                 |
| Package 1 Height             | 1.18 in (3.0 cm)  |
| Package 1 Width              | 4.53 in (11.5 cm) |
| Package 1 Length             | 5.31 in (13.5 cm) |
| Package 1 Weight             | 3.92 oz (111.0 g) |
| Unit Type Of Package 2       | S02               |

| Number Of Units In Package 2 | 24                     |
|------------------------------|------------------------|
| Package 2 Height             | 5.91 in (15.0 cm)      |
| Package 2 Width              | 11.81 in (30.0 cm)     |
| Package 2 Length             | 15.75 in (40.0 cm)     |
| Package 2 Weight             | 6.37 lb(US) (2.888 kg) |

## Sustainability Screen Premium

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

#### Well-being performance

Mercury Free

Rohs Exemption Information Yes

#### **Certifications & Standards**

| Reach Regulation         | REACh Declaration   |
|--------------------------|---|
| Eu Rohs Directive        | Compliant with Exemptions   |
| China Rohs Regulation    | China RoHS declaration  |
| Environmental Disclosure | Product Environmental Profile   |
| Weee                     | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Circularity Profile      | End of Life Information   |