Product data sheet

Specifications





contactor TeSys Deca - 3 poles -AC-3 440V 65 A - coil 600 V AC

LC1D65X6

Main

| Mann | | |
|--------------------------------|--|--|
| Range | TeSys | |
| Range Of Product | TeSys D | |
| Product Or Component Type | Contactor | |
| Device Short Name | LC1D | |
| Contactor Application | Resistive load Motor control | |
| Utilisation Category | AC-2 AC-1 AC-4 AC-3 | |
| Poles Description | 3P | |
| [Ue] Rated Operational Voltage | Power circuit <= 690 V AC 25400 Hz | |
| [le] Rated Operational Current | 80 A (at <140 °F (60 °C)) at <= 440 V AC AC-1 for power circuit 65 A (at <140 °F (60 °C)) at <= 440 V AC AC-3 for power circuit | |
| [Uc] Control Circuit Voltage | 600 V AC 60 Hz | |

Complementary

| • | | |
|-----------------------------|---|--|
| Motor Power Kw | 30 kW at 440 V AC 50/60 Hz 30 kW at 380400 V AC 50/60 Hz 37 kW at 500 V AC 50/60 Hz | |
| | 37 kW at 660690 V AC 50/60 Hz | |
| | 18.5 kW at 220230 V AC 50/60 Hz | |
| | 30 kW at 415 V AC 50/60 Hz 37 kW at 1000 V AC 50/60 Hz | |
| | 37 KW at 1000 V AC 50/60 HZ | |
| Motor Power Hp | 10 hp at 230/240 V AC 60 Hz for 1 phase motors conforming to CSA | |
| | 10 hp at 230/240 V AC 60 Hz for 1 phase motors conforming to UL | |
| | 20 hp at 200/208 V AC 60 Hz for 3 phases motors conforming to CSA | |
| | 20 hp at 200/208 V AC 60 Hz for 3 phases motors conforming to UL | |
| | 20 hp at 230/240 V AC 60 Hz for 3 phases motors conforming to CSA | |
| | 20 hp at 230/240 V AC 60 Hz for 3 phases motors conforming to UL | |
| | 5 hp at 115 V AC 60 Hz for 1 phase motors conforming to CSA | |
| | 5 hp at 115 V AC 60 Hz for 1 phase motors conforming to UL | |
| | 50 hp at 460/480 V AC 60 Hz for 3 phases motors conforming to CSA | |
| | 50 hp at 460/480 V AC 60 Hz for 3 phases motors conforming to UL | |
| | 50 hp at 575/600 V AC 60 Hz for 3 phases motors conforming to CSA | |
| | 50 hp at 575/600 V AC 60 Hz for 3 phases motors conforming to UL | |
| Compatibility Code | LC1D | |
| Pole Contact Composition | 3 NO | |
| Protective Cover | With | |
| [Ith] Conventional Free Air | 10 A (at 140 °F (60 °C)) for control circuit | |
| Thermal Current | 80 A (at 140 °F (60 °C)) for power circuit | |
| | | |

| Irms Rated Making Canacity | 140 A AC for control eize uit conforming to IEC 60047 F 1 |
|---|---|
| Irms Rated Making Capacity | 140 A AC for control circuit conforming to IEC 60947-5-1 1000 A at 440 V for power circuit conforming to IEC 60947 |
| Rated Breaking Capacity | 1000 A at 440 V for power circuit conforming to IEC 60947 |
| Associated Fuse Rating | 10 A gG for control circuit conforming to IEC 60947-5-1 125 A gG at <= 690 V coordination type 1 for power circuit 125 A gG at <= 690 V coordination type 2 for power circuit |
| Average Impedance | 1 mOhm - Ith 80 A 50 Hz for power circuit |
| Power Dissipation Per Pole | 6.4 W AC-1 |
| [Ui] Rated Insulation Voltage | Control circuit 600 V CSA Control circuit 600 V UL Power circuit 600 V CSA Power circuit 600 V UL Control circuit 690 V IEC 60947-1 Power circuit 690 V IEC 60947-1 |
| Overvoltage Category | III |
| [Uimp] Rated Impulse Withstand Voltage | 8 kV IEC 60947 |
| Safety Reliability Level | B10d = 1369863 cycles contactor with nominal load EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load EN/ISO 13849-1 |
| Mechanical Durability | 6000000 cycles |
| Control Circuit Type | AC 60 Hz |
| Coil Technology | Without built-in bidirectional peak limiting diode suppressor |
| Control Circuit Voltage Limits | 0.30.6 Uc 140 °F (60 °C) drop-out AC 50/60 Hz 0.851.1 Uc 140 °F (60 °C) operational AC 60 Hz |
| Inrush Power In Va | 140 VA cos phi 0.75 (at 68 °F (20 °C)) 160 VA cos phi 0.75 (at 68 °F (20 °C)) |
| Hold-In Power Consumption In Va | 13 VA 50 Hz cos phi 0.3 (at 68 °F (20 °C)) |
| | 15 VA 60 Hz cos phi 0.3 (at 68 °F (20 °C)) |
| Heat Dissipation | 15 VA 60 Hz cos phi 0.3 (at 68 °F (20 °C)) 45 W at 50/60 Hz for control circuit |
| Heat Dissipation Operating Time | |
| | 45 W at 50/60 Hz for control circuit 1226 ms closing |
| Operating Time | 45 W at 50/60 Hz for control circuit 1226 ms closing 419 ms opening |
| Operating Time Maximum Operating Rate | 45 W at 50/60 Hz for control circuit 1226 ms closing 419 ms opening 3600 cyc/h 140 °F (60 °C) Control circuit: screw clamp terminal 1 0.000.01 in² (14 mm²) - cable stiffness: solid without cable end Control circuit: screw clamp terminal 2 0.000.01 in² (14 mm²) - cable stiffness: solid without cable end Control circuit: screw clamp terminal 2 0.000.01 in² (12.5 mm²) - cable stiffness: flexible without cable end Control circuit: screw clamp terminal 2 0.000.00 in² (12.5 mm²) - cable stiffness: flexible without cable end Control circuit: screw clamp terminal 2 0.000.00 in² (12.5 mm²) - cable stiffness: flexible without cable end Control circuit: screw clamp terminal 2 0.000.01 in² (14 mm²) - cable stiffness: flexible without cable end Control circuit: screw clamp terminal 2 0.000.01 in² (14 mm²) - cable stiffness: flexible with cable end Power circuit: connector 1 0.000.05 in² (2.535 mm²) - cable stiffness: solid with cable end Power circuit: connector 1 0.000.05 in² (2.535 mm²) - cable stiffness: solid with cable end Power circuit: connector 1 0.000.05 in² (2.535 mm²) - cable stiffness: flexible without cable end Power circuit: connector 2 0.000.04 in² (2.535 mm²) - cable stiffness: flexible without cable end Power circuit: connector 1 0.000.05 in² (2.535 mm²) - cable stiffness: flexible without cable end Power circuit: connector 1 0.000.05 in² (2.535 mm²) - cable stiffness: flexible without cable end Power circuit: connector 1 0.000.05 in² (2.535 mm²) - cable stiffness: flexible without cable end Power circuit: connector 1 0.000.05 in² (2.535 mm²) - cable stiffness: flexible with cable end Power circuit: connector 1 0.000.05 in² (2.535 mm²) - cable stiffness: flexible with cable end |

| Auxiliary Contacts Type | Mirror contact 1 NC IEC 60947-4-1 Mechanically linked 1 NO + 1 NC IEC 60947-5-1 |
|-------------------------------|---|
| Terminals Description Iso N°1 | (13-14)NO (A1-A2)CO (21-22)NC |
| Minimum Switching Voltage | 17 V for control circuit |
| Minimum Switching Current | 5 mA for control circuit |
| Insulation Resistance | > 10 MOhm for control circuit |
| Non-Overlap Time | 1.5 ms on de-energisation between NC and NO contacts 1.5 ms on energisation between NC and NO contacts |
| Mounting Support | Rail Plate |

Environment

| Standards | EN 60947-5-1 IEC 60947-4-1 CSA C22.2 No 14 EN 60947-4-1 UL 508 |
|--|--|
| | IEC 60947-5-1 |
| Product Certifications | UL LROS (pending) RINA CCC CSA GOST BV GL DNV |
| Ip Degree Of Protection | IP2X IEC 60529 IP2X VDE 0106 |
| Climatic Withstand | IACS E10 exposure to damp heat |
| Permissible Ambient Air Temperature Around The Device | -76176 °F (-6080 °C) storage -40140 °F (-4060 °C) operation 140158 °F (6070 °C) with derating |
| Operating Altitude | 3000 m without derating |
| Fire Resistance | 1562 °F (850 °C) IEC 60695-2-1 |
| Flame Retardance | V1 UL 94 |
| Mechanical Robustness | Shocks contactor opened 10 Gn) Shocks contactor closed 15 gn) Vibrations contactor opened 2 Gn, 5300 Hz) Vibrations contactor closed 4 Gn, 5300 Hz) |
| Height | 5.00 in (127 mm) |
| Width | 2.95 in (75 mm) |
| Depth | 4.69 in (119 mm) |
| Net Weight | 3.09 lb(US) (1.4 kg) |

Packing Units

| Unit Type Of Package 1 | PCE |
|------------------------------|-----|
| Number Of Units In Package 1 | 1 |

Contractual warranty

Warranty

18 months

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Reach Free Of Svhc
 Toxic Heavy Metal Free
 Mercury Free
 Rohs Exemption Information Yes
 Pvc Free

Certifications & Standards

| Eu Rohs Directive | Compliant |
|--------------------------|--|
| | EU RoHS Declaration |
| China Rohs Regulation | China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope) |
| Environmental Disclosure | Product Environmental Profile |
| Weee | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Circularity Profile | End of Life Information |