Product data sheet

Specifications





Contactor, TeSys Deca, 4P(2NO+2NC), AC-1, <=440V, 125A, 120V AC 50/60Hz coil, screw clamp terminal

LC1D80008G7

Main

Range	TeSys
Range Of Product	TeSys Deca
Product Or Component Type	Contactor
Device Short Name	LC1D
Contactor Application	Resistive load
Utilisation Category	AC-1
Poles Description	4P
[Ue] Rated Operational Voltage	Power circuit <= 690 V AC 25400 Hz
[le] Rated Operational Current	125 A (at <140 $^{\circ}$ F (60 $^{\circ}$ C)) at <= 440 V AC AC-1 for power circuit
[Uc] Control Circuit Voltage	120 V AC 50/60 Hz

Complementary

Compatibility Code	LC1D
Pole Contact Composition	2 NO + 2 NC
Protective Cover	Without
[Ith] Conventional Free Air Thermal Current	125 A (at 140 °F (60 °C)) for power circuit
Irms Rated Making Capacity	1100 A at 440 V for power circuit conforming to IEC 60947
Rated Breaking Capacity	1100 A at 440 V for power circuit conforming to IEC 60947
[Icw] Rated Short-Time Withstand Current	640 A 104 $^{\circ}$ F (40 $^{\circ}$ C) - 10 s for power circuit 990 A 104 $^{\circ}$ F (40 $^{\circ}$ C) - 1 s for power circuit 135 A 104 $^{\circ}$ F (40 $^{\circ}$ C) - 10 min for power circuit 320 A 104 $^{\circ}$ F (40 $^{\circ}$ C) - 1 min for power circuit
Associated Fuse Rating	200 A gG at <= 690 V coordination type 1 for power circuit 160 A gG at <= 690 V coordination type 2 for power circuit
Average Impedance	0.8 mOhm - Ith 125 A 50 Hz for power circuit
Power Dissipation Per Pole	12.5 W AC-1
[Ui] Rated Insulation Voltage	Power circuit 600 V CSA Power circuit 600 V UL Power circuit 1000 V IEC 60947-4-1
Overvoltage Category	Ш
Pollution Degree	3
[Uimp] Rated Impulse Withstand Voltage	8 kV IEC 60947
Safety Reliability Level	B10d = 1369863 cycles contactor with nominal load EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load EN/ISO 13849-1

Mechanical Durability	4 Mcycles
Electrical Durability	0.8 Mcycles 125 A AC-1 <= 440 V
Control Circuit Type	AC 50/60 Hz
Coil Technology	Without built-in suppressor module
Control Circuit Voltage Limits	0.851.1 Uc -40131 °F (-4055 °C) operational AC 60 Hz 0.30.6 Uc -40131 °F (-4055 °C) drop-out AC 50/60 Hz 0.81.1 Uc -40131 °F (-4055 °C) operational AC 50 Hz
nrush Power In Va	245 VA 60 Hz cos phi 0.75 (at 68 °F (20 °C)) 245 VA 50 Hz cos phi 0.75 (at 68 °F (20 °C))
Hold-In Power Consumption In Va	26 VA 60 Hz cos phi 0.3 (at 68 °F (20 °C)) 26 VA 50 Hz cos phi 0.3 (at 68 °F (20 °C))
Heat Dissipation	610 W at 50/60 Hz
Operating Time	2035 ms closing 620 ms opening
Maximum Operating Rate	3600 cyc/h 140 °F (60 °C)
Connections - Terminals	Control circuit: screw clamp terminals 2 0.000.00 in ² (12.5 mm ²) - cable stiffness: flexible with cable end Control circuit: screw clamp terminals 1 0.000.00 in ² (12.5 mm ²) - cable stiffness: flexible with cable end Control circuit: screw clamp terminals 1 0.000.01 in ² (14 mm ²) - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 2 0.000.01 in ² (14 mm ²) - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 1 0.000.01 in ² (14 mm ²) - cable stiffness: solid without cable end Control circuit: screw clamp terminals 2 0.000.01 in ² (14 mm ²) - cable stiffness: solid without cable end Control circuit: screw clamp terminals 2 0.000.01 in ² (14 mm ²) - cable stiffness: solid without cable end Power circuit: connector 1 0.010.08 in ² (450 mm ²) - cable stiffness: flexible without cable end Power circuit: connector 2 0.010.04 in ² (450 mm ²) - cable stiffness: flexible without cable end Power circuit: connector 2 0.010.08 in ² (450 mm ²) - cable stiffness: flexible with cable end Power circuit: connector 2 0.010.02 in ² (416 mm ²) - cable stiffness: flexible with cable end Power circuit: connector 1 0.010.08 in ² (450 mm ²) - cable stiffness: flexible with cable end Power circuit: connector 2 0.010.02 in ² (425 mm ²) - cable stiffness: solid without cable end Power circuit: connector 2 0.010.08 in ² (450 mm ²) - cable stiffness: solid without cable end Power circuit: connector 2 0.010.08 in ² (450 mm ²) - cable stiffness: solid without cable end Power circuit: connector 2 0.010.04 in ² (425 mm ²) - cable stiffness: solid without cable end Power circuit: connector 2 0.010.04 in ² (425 mm ²) - cable stiffness: solid without cable end
Tightening Torque	Control circuit 10.62 lbf.in (1.2 N.m) screw clamp terminals flat Ø 6 mm Control circuit 10.62 lbf.in (1.2 N.m) screw clamp terminals Philips No 2 Power circuit 106.21 lbf.in (12 N.m) connector flat Ø 6 to Ø 8 mm Power circuit 106.21 lbf.in (12 N.m) connector hexagonal 0.16 in (4 mm) Control circuit 10.62 lbf.in (1.2 N.m) screw clamp terminals pozidriv No 2
Mounting Support	Rail Plate

Environment

Standards	EN 60947-4-1 EN 60947-5-1 IEC 60947-4-1 IEC 60947-5-1 UL 60947-5-1 UL 60947-5-1 CSA C22.2 No 60947-4-1 CSA C22.2 No 60947-5-1 GB/T 14048.4
Product Certifications	UL CSA CCC EAC UKCA CB EU-RO-MR by DNV-GL

Ip Degree Of Protection	IP20 front face IEC 60529	
Protective Treatment	THIEC 60068-2-30	
Climatic Withstand	IACS E10 exposure to damp heat	
Permissible Ambient Air Temperature Around The Device	-40140 °F (-4060 °C) 140158 °F (6070 °C) with derating	
Operating Altitude	03000 m	
Fire Resistance	1562 °F (850 °C) IEC 60695-2-1	
Flame Retardance	V1 UL 94	
Mechanical Robustness	Vibrations contactor open 2 Gn, 5300 Hz) Shocks contactor open 8 Gn for 11 ms) Vibrations contactor closed 3 Gn, 5300 Hz) Shocks contactor closed 10 Gn for 11 ms)	
Height	5.00 in (127 mm)	
Width	3.78 in (96 mm)	
Depth	5.51 in (140 mm)	
Net Weight	4.06 lb(US) (1.84 kg)	

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	4.33 in (11.000 cm)
Package 1 Width	5.31 in (13.500 cm)
Package 1 Length	6.10 in (15.500 cm)
Package 1 Weight	3.94 lb(US) (1.785 kg)
Unit Type Of Package 2	\$02
Number Of Units In Package 2	5
Package 2 Height	5.91 in (15 cm)
Package 2 Width	11.81 in (30 cm)
Package 2 Length	15.75 in (40 cm)
Package 2 Weight	20.24 lb(US) (9.182 kg)
Unit Type Of Package 3	P06
Number Of Units In Package 3	80
Package 3 Height	29.53 in (75.000 cm)
Package 3 Width	23.62 in (60.000 cm)
Package 3 Length	31.50 in (80.000 cm)
Package 3 Weight	341.54 lb(US) (154.920 kg)

Contractual warranty

Warranty

18 months

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Reach Free Of Svhc
Toxic Heavy Metal Free
Mercury Free
Rohs Exemption Information Yes
Pvc Free

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	No need of specific recycling operations