



Panelboard interior, NF, main lugs, 125A, Al bus, 30 pole spaces, 3 phase, 4 wire, 600Y/347VAC max

NF430L1

Main

Panelboard Type	Main lugs
Branch Circuit Breaker Type	EDB/EDG/EDJ
Busbar Material	Aluminium

Complementary

Complementary			
Number Of Spaces	30		
Enclosure Nominal Height	44 in (1117.60 mm)		
	32 in (812.80 mm)		
Enclosure Nominal Width	20 in (508.00 mm)		
Enclosure Nominal Depth	5.75 in (146.05 mm) NEMA 1		
	6.5 in (165.10 mm) NEMA 3R/5/12		
[In] Rated Current	125 A		
[lu] Rated Interrupted Current 65 kA			
Wiring Configuration	4-wire		
umber Of Phases 3 phases			
Voltage Rating	600Y/347 V AC		
Connections - Terminals	Lug line AWG 6AWG 2/0 aluminum/copper		
	Lug neutral AWG 6AWG 2/0 aluminum		
Tightening Torque	40.0150.01 lbf.in (4.525.65 N.m) 0.020.10 in² (13.3067.43 mm²) AWG		
	6AWG 2/0)		
	100.01 lbf.in (11.3 N.m) 0.020.10 in2 (13.3067.43 mm2) AWG 6AWG 2/0)		
	274.99 lbf.in (31.07 N.m) 0.020.27 in ² (13.30177.3 mm ²) AWG 6350 kcmil)		
	274.99 lbf.in (31.07 N.m) 0.020.20 in ² (13.30126.7 mm ²) AWG 6250 kcmil)		
	274.99 lbf.in (31.07 N.m) 0.170.24 in² (107.2152 mm²) AWG 4300 kcmil)		
Height	27 in (685.80 mm)		
Width	10.44 in (265.18 mm)		

Environment

Standards	UL 67
	CSA C22.2

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	6.42 in (16.3 cm)
Package 1 Width	13.90 in (35.3 cm)

Package 1 Length	32.60 in (82.8 cm)
Package 1 Weight	17.24 lb(US) (7.82 kg)



Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance


⊘	Reach Free Of Svhc	
Ø	Toxic Heavy Metal Free	
9	Mercury Free	
⊘	Rohs Exemption Information	Yes

Certifications & Standards


Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Dimensions Drawings

Approximate Dimensions



*FOR ENCLOSURES WHERE DIMENSION "H" IS 26.00/[660], THIS DIMENSION IS 11.00/[279]



ENDWALL WITH KNOCKOUTS (OTHER ENDWALL IS BLANK)

MAXIMUM MAIN LUG	MAXIMUM NUMBER OF	Н		A	
AMPERE RATING	CIRCUITS	IN	MM	IN	MM
125	18	26.00	660	21.00	533
	30	32.00	813	27.00	686
	42	38.00	965	33.00	838
	54	44.00	1118	39.00	991
	30	38.00	965	33.00	838
250	42	44.00	1118	39.00	991
250	54	50.00	1270	45.00	1143
	66	62.00	1575	57.00	1448
	18	26.00	660	21.00	533
125 WITH	30	32.00	813	27.00	686
SUB-FEED LUGS	42	38.00	965	33.00	838
	54	44.00	1118	39.00	991
	30	38.00	965	33.00	838
250 WITH	42	44.00	111B	39.00	991
SUB-FEED LUGS	54	50.00	1270	45.00	1143
	66	62.00	1575	57.00	1448
	18	32.00	813	27.00	686
125 WITH	30	38.00	965	33.00	838
FEED-THRU LUGS	42	44.00	1118	39.00	991
	54	50.00	1270	45.00	1143
	30	50.00	1270	45.00	1143
250 WITH	42	56.00	1422	51.00	1295
FEED-THRU LUGS	54	62.00	1575	57.00	1448
	66	74.00	1880	69.00	1753
	30	56.00	1422	51.00	1295
250 WITH	42	62.00	1575	57.00	1448
SUB-FEED BREAKERS	54	68.00	1727	63.00	1600
	66	74.00	1880	69.00	1753