

Panelboard service entrance, NQ, main breaker, 300A, 42 pole spaces, 1 phase, 2 wire, flush mount, 20 in

NQSE142300F

Main

Range	NQ
Product Or Component Type	Loadcentre
Cover Type	Flush cover

Complementary

o impromontary	
[In] Rated Current	300 A
[Ue] Rated Operational Voltage	120/240 V AC
Mounting Mode	Flush-mounted
Device Mounting	Flush
Poles Description	2-pole
Max Incoming Wire Gauge	AWG 1/0 aluminum/copper
Loadcentre Type	Main Breaker
Number Of Spaces	42
Network Number Of Phases	1 phase
Wiring Configuration	2-wire
Enclosure Material	Galvanized steel
Height	62 in (1574.80 mm)
Width	20 in (508.00 mm)
Depth	5.75 in (146.05 mm)

Environment

Product Certifications	CSA
Nema Degree Of Protection	NEMA Type 1 indoor)

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	7.00 in (17.78 cm)
Package 1 Width	23.50 in (59.69 cm)
Package 1 Length	65.00 in (165.1 cm)
Package 1 Weight	116.01 lb(US) (52.62 kg)

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Well-being performance

	Reach Free Of Svhc	
	Toxic Heavy Metal Free	
	Mercury Free	
	Rohs Exemption Information	Yes
Eu F	Rohs Directive	Compliant
		EU RoHS Declaration
Chir	na Rohs Regulation	China RoHS declaration
		Pro-active China RoHS declaration (out of China RoHS legal scope)