

Product data sheet

Specifications



Panelboard service entrance, NQ, main breaker, 300A, 84 pole spaces, 1 phase, 2 wire, flush mount, 22 in

NQSE184300F

Main

Range	NQ
Product Or Component Type	Loadcentre
Cover Type	Flush cover

Complementary

[In] Rated Current	300 A
[Ue] Rated Operational Voltage	120/240 V AC
Mounting Mode	Flush-mounted
Device Mounting	Flush
Poles Description	2-pole
Max Incoming Wire Gauge	AWG 1/0 aluminum/copper
Loadcentre Type	Main Breaker
Number Of Spaces	84
Network Number Of Phases	1 phase
Wiring Configuration	2-wire
Enclosure Material	Galvanized steel
Height	64 in (1625.60 mm)
Width	22 in (558.80 mm)
Depth	5.75 in (146.05 mm)

Environment

Product Certifications	CSA
Nema Degree Of Protection	NEMA Type 1 indoor)

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	64.02 in (162.6 cm)
Package 1 Width	22.01 in (55.9 cm)
Package 1 Length	5.75 in (14.6 cm)
Package 1 Weight	141.00 lb(US) (63.957 kg)

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Sustainability

Green Premium™ label is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product’s sustainability >](#)

Well-being performance

✓	Reach Free Of Svhc	
✓	Toxic Heavy Metal Free	
✓	Mercury Free	
✓	Rohs Exemption Information	Yes
Reach Regulation		REACH Declaration
Eu Rohs Directive		Compliant EU RoHS Declaration
China Rohs Regulation		China RoHS declaration