# **Product data sheet**

Specifications







Straight length, Powerbus busway, max 100A rated, 600VAC, 3 phase, 4 wire, 4A config, 4ft

PBCE4A100AST048B

#### Main

Product Or Component Type	Straight length
Range Of Product	Powerbus

## Complementary

•	
[In] Rated Current	100 A
Busbar Configuration	4A L1 + L2 + N + L3
Busbar Material	Silver plated copper: busbar
Integral Ground	50 percent capacity integral ground bus
Voltage Rating	600 V AC
Number Of Phases	3 phases
Wiring Configuration	4-wire (100 percent neutral)
Length	4 ft (1.22 m)
Enclosure Material	Painted aluminium black
Number Of Openings	3 each side

#### **Environment**

Ip Degree Of Protection IP40

### **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Weight	13.00 lb(US) (5.897 kg)



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

#### Well-being performance



Mercury Free



Rohs Exemption Information

Yes

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration  Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information