



# Mini circuit breaker, QO, 32A, 1 pole, 240/415VAC, 3kA, bolt on

QOBXD132

## Main

Product	Miniature circuit-breaker
Range	QO
Current Rating	32 A
Voltage Rating	240/415 V AC
Mounting Type	Bolt-on
Number Of Poles	1P
Circuit Breaker Type	Standard
Ratings	Not rated
Electrical Connection	Pressure plate

# Complementary

Interrupt Rating	Icu 3 kA 240/415 V AC IEC 947-2	
Number Of Panel Spaces	1	_
Tightening Torque	44.25 lbf.in (5 N.m) 0.020.04 in² (1025 mm²) AWG 8AWG 2)	_
Height	2.99 in (76 mm)	_
Width	0.75 in (19 mm)	_
Depth	2.91 in (74 mm)	_
Net Weight	0.31 lb(US) (0.141 kg)	_

#### **Environment**

Certifications	IEC
Ambient Rating	104 °F (40 °C)

# **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	3.30 in (8.382 cm)
Package 1 Width	0.70 in (1.778 cm)
Package 1 Length	3.30 in (8.382 cm)
Package 1 Weight	4.96 oz (140.614 g)



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



RoHS/REACh

## Well-being performance

<b>⊘</b>	Toxic Heavy Metal Free	
<b>Ø</b>	Mercury Free	
<b>⊘</b>	Rohs Exemption Information	Yes
<b>⊘</b>	Halogen Free Product	

## **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration  Product out of China RoHS scope. Substance declaration for your information
Circularity Profile	No need of specific recycling operations