# **Product data sheet**





## **Enclosed switch** disconnector, TeSys Control, for ON/emergency stop, 16A,IP65,compact size

VCFN20GE

### Main

Range	TeSys
Product Name	TeSys Mini-VARIO
Device Short Name	VCFN
Product Or Component Type	Emergency stop switch disconnector
Performance Level	Standard
Poles Description	3P
Control Type	Rotary handle
Handle Colour	Red
Handle Front Plate Colour	Yellow
Rotary Handle Padlocking	1 to 3 padlocks 0.160.31 in (48 mm)

### **Complementary**

Complementary	
Marking	0 - 1
[Ue] Rated Operational Voltage	690 V AC
[Uimp] Rated Impulse Withstand Voltage	8 kV
[Ithe] Conventional Enclosed Thermal Current	16 A
[le] Rated Operational Current	11 A AC-23A)400 V
Rated Operational Power In W	5.5 kW 400 V AC-23) 4 kW 400 V AC-3)
Intermittent Duty Class	30
Making Capacity ( I Rms)	200 A 400 V AC-21A 200 A 400 V AC-22A 200 A 400 V AC-23A
[Icm] Rated Short-Circuit Making Capacity	0.5 kA 400 V at Ipeak
[Icw] Rated Short-Time Withstand Rms Current	140 A 400 V 1 s
Rated Conditional Short-Circuit Current	6 kA 400 V 20 A aM 6 kA 400 V 20 A gG
Breaking Capacity	200 A 400 V AC-21A) 200 A 400 V AC-22A) 200 A 400 V AC-23A)
Mechanical Durability	50000 cycles
Electrical Durability	30000 cycles DC-15 50000 cycles AC-21
Suitability For Isolation	Yes

Apr 25, 2024 Life Is On Schneider

Connections - Terminals	Control circuit connector 0.01 in² (4 mm²) flexible with cable end Control circuit connector 0.01 in² (4 mm²) solid
Tightening Torque	Control circuit 6.20 lbf.in (0.7 N.m) connector
Fire Resistance	1760 °F (960 °C) IEC 60595-2-1
Handle Front Plate Dimension	60 x 60 mm
Height	5.16 in (131 mm)
Width	3.25 in (82.5 mm)
Depth	4.17 in (106 mm)
Net Weight	0.93 lb(US) (0.422 kg)

### **Environment**

Standards	IEC 60947-4-1
Protective Treatment	TC
Mechanical Robustness	Vibrations 10150 Hz 1 gn) IEC 60068-2-6 Shocks 11 ms 30 Gn) IEC 60068-2-27
Ambient Air Temperature For Operation	-4122 °F (-2050 °C)

## **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	3.35 in (8.500 cm)
Package 1 Width	4.53 in (11.500 cm)
Package 1 Length	5.31 in (13.500 cm)
Package 1 Weight	10.72 oz (304.000 g)
Unit Type Of Package 2	S02
Number Of Units In Package 2	7
Package 2 Height	5.91 in (15.000 cm)
Package 2 Width	11.81 in (30.000 cm)
Package 2 Length	15.75 in (40.000 cm)
Package 2 Weight	5.25 lb(US) (2.381 kg)

## **Contractual warranty**

Warranty 18 months



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

### Well-being performance

✓ Toxic Heavy Metal Free
 ✓ Mercury Free
 ✓ Rohs Exemption Information

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration  Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	No need of specific recycling operations