

Product data sheet

Specifications



Disconnect switch, TeSys VLS,
auxiliary contact block, 1 normally
closed and 1 normally open, DIN rail

VLSA11RS

Main

Range	TeSys
Device Short Name	VLSA
Product Or Component Type	Auxiliary contact block
Performance Level	High performance
Contacts Type And Composition	1 NC + 1 NO
Contact Operation	Simultaneous 1 NC Simultaneous 1 NO
Range Compatibility	TeSys TeSys VARIO LS VLSA TeSys TeSys VARIO LS VLS3P TeSys TeSys VARIO LS VLS1P
Network Type	DC AC
Network Frequency	50/60 Hz

Complementary

Mounting Location	Right Left
Main Device Mounting Support	DIN rail
[Ue] Rated Operational Voltage	690 V AC 50/60 Hz
[Uimp] Rated Impulse Withstand Voltage	8 kV
[Ith] Conventional Free Air Thermal Current	10 A (at 131 °F (55 °C))
[Ithe] Conventional Enclosed Thermal Current	10 A
[Ie] Rated Operational Current	6 A AC-15)24 V AC 6 A AC-15)48 V AC 6 A AC-15)127 V AC 3 A AC-15)240 V AC 3 A DC-13)24 V DC 1.5 A DC-13)48 V DC 0.55 A DC-13)127 V DC 0.27 A DC-13)240 V DC
Minimum Output Current	10 mA
Minimum Output Voltage	5 V
Connections - Terminals	Control circuit screw clamp terminals 0.00 in² (2.5 mm²) flexible - without cable end
Tightening Torque	Control circuit 7.08...8.85 lbf.in (0.8...1 N.m) screw clamp terminals
Height	2.86 in (72.6 mm)
Width	0.35 in (9 mm)
Depth	1.82 in (46.2 mm)

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Net Weight	0.07 lb(US) (0.03 kg)
Colour	Grey

Environment

Standards	UL 508 CSA C22.2 No 14 IEC 60947-3 IEC 60947-5
Product Certifications	cULus GL
Ip Degree Of Protection	IP20 IEC 60529
Mechanical Robustness	Vibrations 2...100 Hz Fc 0.7 g) IEC 60068-2-6 Shocks 11 ms Ea 15 gn) IEC 60068-2-27
Ambient Air Temperature For Operation	-13...131 °F (-25...55 °C)
Fire Resistance	1562 °F (850 °C) IEC 60695-2-11

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	1.18 in (3.000 cm)
Package 1 Width	2.56 in (6.500 cm)
Package 1 Length	3.15 in (8.000 cm)
Package 1 Weight	1.31 oz (37.000 g)
Unit Type Of Package 2	S01
Number Of Units In Package 2	30
Package 2 Height	5.91 in (15.000 cm)
Package 2 Width	5.91 in (15.000 cm)
Package 2 Length	15.75 in (40.000 cm)
Package 2 Weight	2.92 lb(US) (1.326 kg)

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)

Well-being performance

✓	Reach Free Of Svhc	
✓	Toxic Heavy Metal Free	
✓	Mercury Free	
✓	Rohs Exemption Information	Yes
Reach Regulation		REACH Declaration
Eu Rohs Directive		Compliant EU RoHS Declaration
China Rohs Regulation		China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)